



From the Makers of the Ashford Formula™
and the RetroPlate® System

PRODUCT NAME

CreteClean Plus with Scar Guard™

BENEFITS

Revolutionary, Cutting Edge Technology

CreteClean Plus with Scar Guard is uniquely formulated to clean and condition densified and densified-polished concrete. Proprietary polar technology pulls contaminants out and up from concrete and holds it in suspension, providing maximum cleaning efficiency.

Reduces Environmental Impact

CreteClean Plus with Scar Guard is a water-based detergent that contains no Volatile Organic Compounds (VOCs). Due to its high concentration, less product is required for use, and therefore less needs to be purchased, shipped, and stored, thereby greatly reducing its overall environmental impact.

Improves Floor Performance

The chemically advanced technology of CreteClean Plus with Scar Guard elevates it from a detergent to a performance enhancing cleaning agent. Regular and frequent use of CreteClean Plus with Scar Guard can, over time:

- + Help strengthen and harden concrete surfaces,
- + Decrease the visibility of minor scratches and blemishes,
- + Decrease porosity, and
- + Help maintain the sheen of densified concrete surfaces.

Suitable For Use In Food Handling Establishments

CreteClean Plus with Scar Guard is approved for use in institutional, industrial and food handling establishments.

TECHNICAL DATA

Form:	Clear, Green Liquid with Fresh Scent Weighs 8.5 lbs / gal (1.02 kg / L)
Flashpoint:	Not Applicable
Freezing:	If product freezes, agitate to re-emulsify
pH:	11.0 - 12.0 (Concentrate) 9.0 - 9.5 (Diluted for Use)
Packaging:	55 gal (208 L) Drums 5 gal (19 L) Pails
Storage Life:	Two (2) Years
Dilution:	General Cleaning 1 oz CreteClean Plus / gal of H ₂ O (31.2 - 39 mL / L) Poultice Cleaning 4 oz CreteClean Plus / gal of H ₂ O (7.8 mL / L)

DIRECTIONS

CreteClean Plus with Scar Guard is simple and easy to use. First, remove any debris from the area to be cleaned. CreteClean Plus can then be applied by wet mop*, automatic scrubber or other means. Remove any excess diluted CreteClean Plus and allow the concrete surface to air-dry.

For enhanced results on concrete that has been treated with the Ashford Formula™ or RetroPlate® System, periodically burnish or buff the surface with a non-aggressive pad or polishing pad. *To avoid streaking, use only a rayon mop head and change cleaning solution every 800 - 1,000 ft² (244 - 305 m²).

*POULTICE CLEANING PROCEDURES FOR SEVERE OIL STAINING

Remove all loose soil and fine grit. Mop down CreteClean Plus diluted at 4 oz / gal of water (7.8 mL / L). Agitate the solution to assist the product in penetrating the soil's surface. Cover the wet surface with plastic film and tape down edges. Allow area to remain wet for 10 - 15 minutes or longer if possible. Remove the plastic film and dispose of soiled solution. The procedure may need to be repeated if soil leaches back to the surface as the concrete completely dries out.

Note: This procedure is designed for spot removal of significant oil or grease staining. It is not a cleaning procedure.

SPECIAL CONSIDERATIONS

Several applications of CreteClean Plus with Scar Guard may be needed to remove oil stains from concrete surfaces that have severe oil staining. Additional treatment with an oil emulsifier, such as **CreteStrip™***, may be necessary.

Additionally, acids, salts, deicers and other harmful substances should be promptly removed to avoid damage to your floor. A proper, regular and frequent maintenance program is highly recommended. Making CreteClean Plus with Scar Guard a regular part of your maintenance program will ensure superior results.

*CreteStrip is manufactured exclusively by Curecrete Distribution, Inc. For details visit www.curecrete.com.

EXTENDED MANUFACTURER WARRANTY

Due to the superior performance achieved by regularly using CreteClean Plus with Scar Guard, concrete surfaces treated with the Ashford Formula™ or RetroPlate® System can qualify for an extension of their original Manufacturer Warranty to a Lifetime Warranty. Qualifying conditions apply. Contact Curecrete Distribution, Inc. for more information.

Curecrete Distribution, Inc. warrants this product to be free from any manufacturing defects.

TECHNICAL ASSISTANCE

For technical support and additional cleaning tips and suggestions, please contact the Technical Service Department of Curecrete Distribution, Inc. at **801.489.5663**, toll free at **800.998.5664**, or by email at info@curecrete.com.

To purchase or reorder CreteClean Plus with Scar Guard, please contact WAXIE Sanitary Supply toll free at **800.995.4466**.

CreteClean Plus with Scar Guard - Data Sheet RV 3-2013