



DIRECTIONS FOR USE

AUTOMATIC SCRUBBER AND MOP & BUCKET

+ AUTO SCRUBBER DILUTION RATIO

1 oz CreteClean Plus with Scar Guard	1 gal Water	7.8 mL CreteClean Plus with Scar Guard	1 L Water
Cleaning Surface Area 500 ft² / gal		Cleaning Surface Area 12.3 m² / L	

+ MOP & BUCKET DILUTION RATIO

1 oz CreteClean Plus with Scar Guard	1 gal Water	7.8 mL CreteClean Plus with Scar Guard	1 L Water
Cleaning Surface Area 800 - 1,000 ft² / gal		Cleaning Surface Area 244 - 305 m² / L	

Recommended cleaning: 3 times per week.

1 SWEEP THE FLOOR

Sweep the floor to remove all loose soil and debris using a dust/dry mop. Pick up soil and debris with a broom and dust pan. *Note: It is best to sweep the floor with a dust/dry mop, as it holds grit and fine particles and takes them off the floor.*

2 FILL AUTO SCRUBBING MACHINE WITH CLEANING SOLUTION

Fill the automatic scrubber with *Crete Clean Plus with Scar Guard™* solution, diluted with water at a ratio of 1 oz / 1 gal (7.8 mL / 1 L).

3 MOVE MACHINE TO AREA THAT NEEDS CLEANING AND AFFIX PADS/BRUSHES

Move the scrubbing machine to the area that needs cleaning. Plan the most appropriate scrub path for the floor. Affix pads/brushes* to the scrubbing machine. **Different color pads/brushes can be used for more aggressive cleaning.*

4 TURN ON SOLUTION VALVE TO MAXIMUM FLOW

Turn on the solution valve to maximum flow. Allow water to commence dripping off the pads/brushes before lowering pad heads/brushes to floor (this will avoid causing donuts on the floor surface). Lower pads/brushes and turn on.

5 TURN ON VACUUM AND ADJUST WATER FLOW

Turn on vacuum, lower squeegee and commence scrub pattern. *Note: This step can be delayed if you are double scrubbing an area (see step 6).* Adjust water flow when machine is moving to avoid flooding and splash.

6 DOUBLE SCRUB (IF NECESSARY)

When a double scrub is required, leave squeegee up and scrub floor without picking up solution on the first pass. Turn and scrub over the same path again with the squeegee lowered to pick up the soiled solution.

7 DISPOSAL OF SOILED SOLUTION

Dispose of the soiled solution according to your local government regulations.

This procedure is good for small or constricted areas, or to clean-up spills. Recommended cleaning: 3 times per week.

1 SWEEP FLOOR

Commence cleaning in most convenient corner and work the designated area to be cleaned.

For Heavily Soiled Areas: Sweep the floor with a concrete broom to help remove concrete fines caused by standard wear. Pick up the residue and dispose.

For Light/Normal Soiled Areas: Dust/dry mop* area to be cleaned. When finished sweeping, lift mop 0.5" to 1" (1.27 cm to 2.54 cm) off the floor and gently shake to remove any grit. Pick up loose soil with broom and dust pan and dispose. **Dust/dry mop must be clean, as a dirty dust/dry mop grinds soil into the floor. Never use a treated dust mop.*

2 WET MOP FLOOR

Dip wet mop* into bucket and wring out to damp. Cleaning solution should just barely drip from mop ends when mop is lifted out of the wringer. **To avoid streaking, use only a rayon mop head.*

3 MOP ONLY DEFINED AREA FOR CLEANING

Define area to be cleaned to eliminate over-mopping and partial cleaning. Use a standard figure eight motion. Flip over, wring, and rinse mop frequently. Change solution according to surface cleaning recommendation above.

4 DISPOSAL OF SOILED SOLUTION

Dispose of the soiled solution according to your local government regulations.

Distributed by:





DIRECTIONS FOR USE

POULTICE CLEANING AND WARRANTY INFO

+ POULTICE DILUTION RATIO

4 oz. CreteClean Plus with Scar Guard	1 gal. Water	31.2 mL CreteClean Plus with Scar Guard	1 L Water
Cleaning Surface Area Treat small areas at a time.		Cleaning Surface Area Treat small areas at a time.	

This procedure is designed for spot removal of significant oil or grease staining. It is not a regular maintenance procedure. Several applications of Crete Clean Plus with Scar Guard™ may be needed to remove oil stains from concrete surfaces that have severe oil staining. Additional treatment with an oil emulsifier, such as CreteStrip™ may be necessary.

*CreteStrip™ is manufactured exclusively by Curecrete Distribution, Inc. For details call toll free 800.998.5664.

1 SELECT SMALL AREA TO BE TREATED

Select area(s) to be poulticed. Remember, although grease and oil may occur all over the floor area, you are best to treat small areas that can be controlled easily.

2 SWEEP THE FLOOR

Remove all loose soil and fine grit using a dust/dry mop. Pick up soil and debris with a broom and dust pan.

3 MOP DOWN AREA WITH SOLUTION

Mop* down Crete Clean Plus with Scar Guard™ diluted at 4 oz / 1 gal (31.2 mL / L). Agitate solution with the mop to assist the product in penetrating the soiled surface. *Use a rayon mop head to avoid streaking.

4 COVER AND ALLOW SOLUTION TO PENETRATE

Cover the wet surface with plastic film and tape down the edges. Allow area to remain wet for 10 - 15 minutes or longer if possible. Do not allow to dry on surface.

5 UNCOVER AND REMOVE SOLUTION

Remove plastic film and pick up soiled solution with a wet/dry vacuum.

6 EXAMINE THE SURFACE

Examine the surface for any signs of grease or oil. A white cloth rubbed on the surface will show a black or dark color if surface oil or grease is present. If soil still remains, repeat steps 3 - 6.

LIFETIME PRODUCT WARRANTY EXTENSION OFFER

Due to the superior performance achieved by regularly using Crete Clean Plus with Scar Guard™, concrete surfaces treated with the Ashford Formula™ or RetroPlate® System can qualify for an extension of their original manufacturer warranty to a Lifetime Product Warranty. Qualifying conditions apply.

WARRANTY EXTENSION QUALIFICATIONS

The floor must be an Ashford Formula™ or RetroPlate® System floor, which is applied to a structurally sound concrete floor surface by a Certified Applicator of Curecrete Distribution, Inc. Unfortunately, we are unable to offer a warranty extension on floors that have not been treated with the Ashford Formula™ or RetroPlate® System.

The floor must be cleaned exclusively with Crete Clean Plus with Scar Guard™ at minimum **3 times per week** and may be alternated with water only.

The floor must be cleaned using the correct processes, procedures and frequency as recommended by Curecrete Distribution, Inc.

HOW TO APPLY FOR A WARRANTY EXTENSION

Contact your Ashford Formula™ or RetroPlate® System Sales Representative (contact information provided on the front side of this sheet).

For floors older than 4 months (from the date of the original manufacturer's warranty issue date), the Sales Representative must first preview and approve the floor for a warranty extension.

Complete the **Warranty Extension Request Form for CreteClean Plus with Scar Guard™** provided by your Sales Representative or by calling Curecrete Distribution, Inc. at 800.998.5664 or 801.489.5663.

Once the request has been received and approved, a warranty extension certificate will be provided to the building owner and the warranty extension will be in effect - extending the original manufacturer's warranty to a Lifetime Product Warranty.

The validity of the extension warranty is contingent upon consistent and exclusive use of Crete Clean Plus with Scar Guard™ 3 times per week, and is void if these requirements are not adhered to. Using another cleaner other than Crete Clean Plus with Scar Guard™ will automatically void the warranty extension.

MSDS

For MSDS information, please visit: http://ashfordformula.com/files/document/CreteClean_Plus_with_Scar_Guard_MSDS.pdf or scan the QR code to the right.



TECHNICAL ASSISTANCE

For technical support, please contact the Technical Service Department of Curecrete Distribution, Inc. at **801.489.5663**, toll free at **800.998.5664** or by email at info@curecrete.com.