

"Original"

SAF-T-STEP®



SAF-T-STEP® Products

SLIP RESISTANT FLOOR CLEANER & TREATMENT

For use on unsealed porous concrete, quarry, ceramic, brick, diamond plate, epoxy, and porcelain floors

Contains KALISITE®

PRODUCT DESCRIPTION:

SAF-T-STEP® Slip Resistant Floor Cleaner and Treatment is a highly effective safety product formulated for use over unsealed porous Concrete, Quarry, Brick, Ceramic tiles and other porous floor surfaces. Unlike other floor maintenance products, SAF-T-STEP® simultaneously removes organic and inorganic deposits and soils, deep cleans and treats the floor, which increases the slip resistance of the floor surface and reduces the potential for slip and fall accidents. SAF-T-STEP® is also an excellent cleaner to remove the heavy soil deposits from grouted floor surfaces. The product leaves no slippery residues on the floor surface. Effective for use on floors in Plants, Athletic Facilities, Hospitals, Kitchens, Restaurants, Hotels, Schools, Shopping Malls, rest room floors, shower floors and anywhere that slips and falls are a problem.

SAF-T-STEP® is classified by Underwriters Laboratories® as to slip resistance.

PRODUCT FEATURES

- Increases Slip Resistance
- Powerful Action
- Safe - D.O.T. Class 55
- Saves Labor
- Easy to Use
- Underwriter's Laboratories® as to Slip Resistance

USER BENEFITS

- Reduces Potential for Slip and Fall Accidents
- Removes Silica and hard water stains, grease & oil from floor pores and grout lines
- Non-hazardous; Non-corrosive, Septic Tank Safe; Degradable
- 2-in1; Safety and Cleaning at the Same Time
- Apply by Brush, Sprayer, Foamer or Automated Equipment
- Demonstrates User's Attempts to Maintain Safer Floors



Classified by Underwriters Laboratories Inc.®
as to Slip Resistance Only. 8L30



A4

123398

DYNAMIC




RESEARCH COMPANY, INC.

FOR ADDITIONAL INFORMATION

DYNAMIC RESEARCH COMPANY, INC.

Safety Products Division
4800 SW Meadows Road - Suite 300
Lake Oswego, Oregon 97035
503-699-1335 FAX 503-699-1094
Order Desk: 800-876-2232
URL <http://www.saf-t-step.com>

SAF-T-STEP® Slip Resistant Floor Cleaner & Treatment



"SHOCK" SLIP TREATMENT PROCEDURE (as needed)

Use SAF-T-STEP® Slip Resistant Treatment full strength whenever floor surface is out of control with heavy stains or grease build-ups. Pretest glazed tile floors before using. NOTE: On new floors or lightly soiled floors, "SHOCK" cleaning procedure is not recommended; use "daily" slip treatment.

"DAILY" SLIP TREATMENT AND CLEANING PROCEDURES

Dilute 2 to 4 ounces SAF-T-STEP® Slip Resistant Treatment per gallon of water. If using an auto scrubber, add defoamer to recovery tank. If using a foam gun, SAF-T-STEP® will self foam at 4 ounces of water dilution.

DIRECTIONS

1. Apply product liberally, evenly and directly to floor. Leave product on floor for 5 minutes.
2. Scrub floor with stiff bristle brush; pay special attention to grout lines and heavy soiled areas.
3. Rinse thoroughly with clean water.
4. Squeegee remaining water and residue to floor drains. If drains are not available, wet vac or mop-up with mop, bucket and clean water.