

# Pure Performance Floor Care Products

# PURE ARMOR

## FLOOR FINISH

Pure Armor Floor Finish is part of the Pure Performance Floor Care program. This incredibly tough floor finish is ideal for low maintenance (minimal-buffing), as well as regular (scheduled buffing) applications. Its high performance acrylic and polyethylene polymers produce a beautiful, long lasting shine that resists black marking and scuffing. Pure Armor is ideal for areas such as classrooms, patient rooms and offices. If desired, Pure Armor responds to periodic spray buffing or high speed burnishing with equipment ranging from 175 rpm to propane burnishers.

**Packaging:** 2x2½ Gal. Containers

**Product coverage rate:** Up to 3,000 sq. ft. per gallon

**ITEM #930165**



The next generation in floor care solutions



This product meets the Green Seal™ standard for industrial and institutional floor care products based on its reduced human and aquatic toxicity and reduced smog production potential

**WAXIE'S**  
SANITARY SUPPLY

# Pure Performance Floor Care Products

# PURE ARMOR FLOOR FINISH

Features	Advantages	Benefits
<b>High Durability</b>	Offers a long lasting shine as a result of superb scuff and black mark resistance.	Less maintenance required.
<b>Ultra High Gloss</b>	Pure Armor has outstanding initial lay down gloss and is the perfect product for both high speed burnish and no-burnish floor care systems.	With a high off-the-mop shine, where time and equipment may not be available to burnish the floor, Pure Armor provides an excellent option where our product can work well with a UHS burnish program or without.
<b>Compressed Zinc-Free Interlinking Technology</b>	Produces a more tightly cross-linked film.	Increases durability and improves lay-down gloss.
<b>Ultra-Clear Resin Technology</b>	The polymers used in this finish do not fog or haze like many of the other products available. Being clear allows for extended service life, due to the finish maintaining a clean and clear look.	Reduced stripping, along with scrub and recoat cycles, which reduces the overall maintenance cost with this product.
<b>High Solids = High Performance Throughout</b>	This floor finish is designed to provide extended service life, even under the most severe traffic conditions.	Works well in both regular maintenance conditions, as well as reduced maintenance conditions. Being durable means that it can stand up under tough traffic conditions and minimal maintenance.
<b>Black Heel Mark Resistance (BHMR)</b>	Very good black heel mark resistant (BHMR). Excellent scuff resistance.	Greater trouble-free life, with minimal cost associated with maintenance.
<b>Repairable</b>	The finish is engineered to be easily buffed with the full selection of floor maintenance equipment (Electric, Battery, Propane) without any degradation to the finish or its service life.	Fits well into any maintenance operation and performs well in all environmental conditions.
<b>Fast Drying</b>	Dry times under 30 minutes, allows for faster application of multiple coats to complete job.	Faster dry times means less downtime between coats.
<b>Green Seal™ GS-40 Certified</b>	Performs like a standard floor finish without the need for zinc and other impactful chemicals	Reduced impact on environment and users.

(800) 995-4466  
www.waxie.com



**Corporate Headquarters**  
9353 Waxie Way  
San Diego, CA 92123

# PURE ARMOR FLOOR FINISH

ITEM #930165

## TRAINING

### Directions

#### **APPLICATION:**

1. Strip floors to remove old waxes, sealers and finishes using WAXIE-Green Floor Stripper or Pure Annihilator Floor Stripper.
2. Rinse thoroughly using Balance Neutral pH Cleaner diluted with water at 2 ounces per gallon and let dry.
3. With clean equipment and an appropriate finish mop, apply thin, even coats of Pure Armor finish to the floor.
4. Allow to dry thoroughly between coats (time varies with humidity).
5. Application of more than four coats of finish within a 24 hour period should be done so with caution. Applying too many coats too quickly could cause undesirable results.

**NOTE:** For stripping and maintaining asbestos containing tile, follow OSHA or EPA guidelines.

**COVERAGE:** One gallon covers up to 3,000 square feet.

#### **MAINTENANCE:**

1. **DAILY:** Sweep or dust mop as necessary to remove gritty soil.
2. **DIRTY FLOORS:** Clean with 1-3 ounces of Balance Neutral pH Cleaner per gallon of water.
3. **RESTORATIVE:** Mop-on or auto-scrub the entire surface area using Pure Rejuvenator Cleaner and Restorer, diluted at 2-4 ounces per gallon of water. Let dry and burnish the entire floor surface with high speed machine and WAXIE Pure Performance Microfiber Burnishing Pad or natural hair pad.
4. **PERIODIC SCHEDULED STRIP OUT:** Ordinarily, stripping is not required more than (1) or (2) times per year. Use WAXIE-Green Floor Stripper or Pure Annihilator Floor Stripper when this is required.



This product meets the Green Seal™ standard for industrial and institutional floor care products based on its reduced human and aquatic toxicity and reduced smog production potential.



Not formulated with butyl, harsh alkalies, zinc, phthalates or APEO surfactants.

#### **DISPOSAL**

**PRODUCT:** Dispose of excess product in accordance with local, state, and federal regulations.

**CONTAINER:** Please recycle HDPE container.

#### **VENTILATION**

No special ventilation needed. However, use of adequate ventilation is good industrial practice.

#### **IMPROPER USE OR APPLICATION**

**IMPROPER USE:** May irritate eyes, skin and gastrointestinal tract. Avoid eye and skin contact.

**IMPROPER APPLICATION:** Over application of finish may cause floor to be tacky, streaked and/or ghosted looking, dull and prone to black marking and scuffing.

#### **FIRST AID**

**EYES & SKIN:** Flush with water (eyes 15 minutes). If irritation persists, seek medical attention.

**INGESTION:** If swallowed, give 2-3 large glasses of water. Seek medical attention.

The next generation in floor care solutions