

# WAXIE Edge-Off Baseboard Wax Stripper



## DESCRIPTION

Use to remove wax build-up from baseboards, floors, and ceramic wall tiles. Special high foaming floor stripper formulation developed to let chemistry do the hard work of removing years of unsightly wax and buildup. Ideal for use on vertical surfaces such as baseboards and kick plates not normally reached with water-thin conventional liquid stripper applications. It is excellent also for spot stripping hard-to-reach vertical and horizontal areas where foot traffic is minimal: under desks, tables, counters, along walls, behind fixtures, etc. This heavy-duty product leaves your floor ready for new wax to be applied. Multiple layers of buildup are quickly emulsified by chemical action for easy, speedy removal. Uses can be found in most any commercial setting including offices, institutions, hotels, hospitals, schools, public places and more.

## SPECIFICATIONS

### AS SOLD

Appearance .....	Brown liquid propelled by compressed gas
Odor .....	Pine scent
pH.....	No data available
Melting Point/Freezing Point .....	No data available
Initial Boiling Point/Boiling Range .....	28°C (84°F)
Flash Point .....	-104.4°C (-156°F)
Flammability .....	Extremely flammable aerosol
Relative Density .....	0.923 (7.70 lb./gal)
Solubility .....	No data available
VOC .....	No data available

### ACTIVE INGREDIENTS:

2-Butoxyethanol.....	10–25%
Butane .....	2.5–10%
Propane .....	1.0–2.5%
Oils, Pine.....	0.1–1.0%
Ethylene Glycol .....	0.1–1.0%
EDTA Tetrasodium Salt .....	0.1–1.0%

**OTHER INGREDIENTS:** ..... Balance

**SHELF LIFE:** All WAXIE brand chemical products have a guaranteed shelf life of up to one year after the date product was manufactured, when stored in ambient conditions. The actual manufacturing date is included in a date code on every product container.

Item: 320971

Net Weight: 19 oz. in 20 oz. can 12/cs

## APPLICATION



## FEATURES & BENEFITS

- Clinging high foam
- Easy rinsing
- Excellent spot stripper
- Pine fragrance

# WAXIE Edge-Off Baseboard Wax Stripper

## DIRECTIONS FOR USE

Shake well before using. Check the product on a small inconspicuous area of the surface to be sprayed to make sure there is no attack. Do not spray on painted or varnished surfaces. Wipe off any overspray immediately. Turn can UPSIDE DOWN and hold 6–10 inches from baseboard or surface to be sprayed. A thin even coating should cover the wax. Wait 3–5 minutes, longer in case of substantial build-up. Wet scrub the surface with an abrasive pad or scrub brush. Repeat until all wax is removed. Rinse surface with clean water and allow area to dry thoroughly before re-polishing.

## SAFETY INFORMATION

### PERSONAL PROTECTIVE EQUIPMENT:

**Ready-to-Use** Occupational Use situations. Safety Glasses & Gloves if skin contact is anticipated.



Read the Safety Data Sheet (SDS) and product label before use. The SDS and product label contain hazard warnings, precautionary statements and first aid procedures. SDS documents are available online at [www.waxie.com](http://www.waxie.com) or by calling (800) 995-4466.

For sale to, use and storage by service professionals only. Keep out of reach of children.

**HOTLINE NUMBER:** You may contact Chem-Tel at (800) 255-3924 for emergency medical treatment information.



The Most Trusted Name In Clean. Since 1945.

Corporate Headquarters | 9353 Waxie Way | San Diego, CA 92123

(800) 995-4466 | [www.waxie.com](http://www.waxie.com)

© 2023 WAXIE Sanitary Supply 0623