


WAXIE Defoamer Foam Dissipater



Item: 1070324 gl 4/cs
Secondary Label: 1070324LBL

APPLICATION



FEATURES & BENEFITS

- Highly concentrated at 1 oz/10 gal
- Protects vacuum motors

DESCRIPTION

Dissipates foam in autoscrubbers, wet vacs and extraction machines; protects vacuum motors from foam damage.

SPECIFICATIONS

	AS SOLD	USE DILUTION
Appearance	Opaque, white	Clear, colorless liquid
Odor	Odorless	Odorless
pH	6.5-8.5	Approx. 7.0
VOC	N/A	N/A
Melting Point/Freezing Point	< 0°C (32°F)	Approx. 0°C (32°F)
Initial Boiling Point/Boiling Range	> 99°C (210°F)	Approx. 100°C (212°F)
Flash Point	> 93°C (> 200°F) [PMCC]	N/A
Flammability	N/A	N/A
Relative Density (Density)	Approx. 1.0	Approx. 1.0
Solubility	Completely soluble in water	Completely soluble in water

ACTIVE INGREDIENT:

Silicone Emulsion 3-7%

OTHER INGREDIENTS:

..... Balance

SHELF LIFE: All WAXIE brand chemical products have a guaranteed shelf life of up to one year after the date product was manufactured, when stored in ambient conditions. The actual manufacturing date is included in a date code on every product container.

DIRECTIONS FOR USE

Pour *WAXIE Defoamer* full strength directly into recovery tank using 1 ounce of *WAXIE Defoamer* per 10 gallons of recovery capacity. When tank is drained, retreat using same dilution ratio. If a large amount of foam is recovered, it may be necessary to increase amount used.

SAFETY INFORMATION

PERSONAL PROTECTIVE EQUIPMENT:		
Concentrate	B – Safety Glasses & Gloves	 
Ready-to-Use	A – Safety Glasses	

Read the Safety Data Sheet (SDS) and product label before use. The SDS and product label contain hazard warnings, precautionary statements and first aid procedures. SDS documents are available online at www.waxie.com or by calling (800) 995-4466.

For sale to, use and storage by service professionals only. Keep out of reach of children.

HOTLINE NUMBER: You may contact Chem-Tel at (800) 255-3924 for emergency medical treatment information.